


MX1-10FEP-D

Embedded System for GPU Computing
Supports Intel® Coffee Lake Xeon / Core-i Powerful Processor


Introduction

MiTAC's MX1-10FEP-D embedded system is the next generation embedded system with Intel® Coffee Lake C246 workstation chipset which can support Xeon and Core-i LGA1151 socket type processor. The excellent performance, powerful processor, OCP/OVP power protection, and expandable design provide the solution for every complicated task and most types of application.

The MX1-10FEP-D's 8.5 liter chassis design and Xpandable module design give it the possibility to implement the complicated tasks and for every workspace and environment. Flexibilities also mean a rich array of I/O ports (including 2 x Ethernet RJ45, 8 x USB, 1 x HDMI, 1 x DVI-I, 1 x DisplayPort, 2 x COM, PCIe X16 + X1 slots, 3-pin Terminal Block Power Input, and 3 x Expansion doors) to add a variety of peripherals. Storage expandability is supported for 3 x high-density hard drives in 2.5" HDD bracket design. The reserved space for dual PCIe slots can be used for 1 x GFX Card installation. Two mPCIe (shared with mSATA) slots provide the support of SSD and wireless interfaces which allow effortless connection to Wi-Fi and Bluetooth networks, and 4Gconnectivity. DIO/COM/LAN/PoE/Power Igniton expansion modules extend the capability and possibility to be used in more applications.



Dimension (mm)



Optional Peripheral

Model Number	Description
MS-48CDN-DT10	Xpansion Module with 4 x RS232 / 422 / 485, 8-bit Isolated DIDO (4 x DI, 4 x DO)
MS-04LAN-R10	Xpansion Module with 4 x Intel i210-IT Giga LAN, RJ45 Port
MS-04LAN-M10	Xpansion Module with 4 x Intel i210-IT Giga LAN, M12 Port
MS-04POE-R10	Xpansion Module with 4 x PoE+, Intel i210-IT Giga LAN, RJ45 Port
MS-04POE-M10	Xpansion Module with 4 x PoE+, Intel i210-IT Giga LAN, M12 Port
ME-02POE-R10	Xpansion Module with 2 x PoE +, Intel i210-IT Giga LAN, RJ45 Port
MS-01IGN-S10	Vehicle Power Ignition Card, 12V/24V and Power ON/OFF Timing Selectable
220W Power Adapter	AC to DC, DC24V / 9.2A, 220W*
300W Power Adapter	AC to DC, DC24V / 12.5A, 300W*

* Safety Operating: 0~40°C, practical Operating: -30~60°C (Over 40°C need derating by 2.5%/°C).

* AC to DC Accessory for industrial application. Not for railway application

MX1-10FEP-D Embedded System for GPU Computing

SYSTEM	
CPU	9th & 8th Gen Intel® Coffee Lake Xeon LGA1151 Socket Processor, 6-core TDP Max. 80W 9th & 8th Gen Intel® Coffee Lake LGA1151 Socket Processor, Core i7/i5/i3 6-core TDP Max. 65W, Core i9 8-core TDP Max 35W
Chipset	Intel® C246
System Memory	DDR4 2666MHz, 2 x 260-pin SO-DIMM, Max. 32GB (Xeon: ECC; Core-i: Non-ECC)
Graphics	Intel® HD Graphics
Display Interface	HDMI, DisplayPort, DVH
Storage Slot	3 x 2.5 HDD / SSD (1 w/ Removable HDD Bay, 2 w/ Internal HDD Bracket) 2 x mSATA
Ethernet	Intel® I219-LM Giga LAN + I210-IT Giga LAN
Audio	Realtek® ALC888
I/O Chipset	Nuvoton NCT6116D
TPM	Nuvoton NPCT750AAAYX
Expansion Slot	Storage: M.2 2242 / 2260 / 2280 M key (PCIe X4 / SATAIII) Storage/LTE/Wireless: 2 x Mini PCIe Full / Half size (USB2.0/ PCIe X1/ SATAIII), w/ SIM Card Holder Wireless: M.2 2230 E key (PCIe X1 / USB2.0) PCIe 3.0 X16, PCIe 3.0 X1 (Option: 2 x PCIe 3.0 X8)
Indicator	Power LED, HDD LED, DIO LED, LAN1 & 2 ACT / SPEED
FRONT I/O	2 x USB 3.2 Gen1
	1 x HDMI 1.4
	2 x SIM Card Slot w/ Cover
	1 x 2.5" SATAIII HDD / SSD Bay
REAR I/O	4 x USB 3..2 Gen2 (Gbps), 2 x USB 2.0, 2 x RJ-45 , 1 x DisplayPort 1.2, 1 x DVH, 1 x PS/2
	2 x RS232 / 422 / 485 (Support Power 5V / 12V), 1 x Mic-in, 1 x Line-out
	1 x 2-pin Terminal Block Remote Power on / off
	1 x 2-pin Terminal Block Remote Power reset
	1 x 4-pin Terminal Block External Fan Connector
	1 x 3-pin Terminal Block Power Input
Edge AI Engine (Optional)	Hailo-8™ M.2 2242 M key (Model Name:M2M-01HAI-MX1)
POWER REQUIREMENT	
Power Input	9~48V Wide Range DC Input w/ Terminal Block Connectivity
MECHANICAL	
Thermal Design	a. Fanless w/o Venting Holes b. With 2 x Internal 40x40x20 System Fan (Supporting NVIDIA GTX1650/GTX1660 Graphic Cards) c. With 2 x Internal 40x40x28 System Fan and Fan Duct (Supporting NVIDIA Tesla T4/P4 GPU Cards)
Mounting / Material	Wallmount / Top cover: Aluminum Alloy , Bezel and chassis: Steel
Dimension	10.6" x 9.7" x 5.0" (268 mm x 246 mm x 128 mm)
ENVIRONMENTAL	
Operating Temperature	35W TDP Processor: -40°C to 70°C 51~65W TDP Processor: -40°C to 50°C / 71~80W TDP Processor: -40°C to 40°C *The operating temperature is based on fanless design w/o GPU card installation. **with 0.7m/s Air Flow and Wide Temperature Memory/Storage
Operating Humidity	10%~90% R/H (Non-condensing)
Vibration Resistance	Operating, 5 Grms, 5-500 Hz, 3 Axes (w/ SSD, according to IEC60068-2-64)
Shock Resistance	Operating, 50 Grms, Half-sine 11 ms Duration (w/ SSD, according to IEC60068-2-27)
Certification	EMC: CE & FCC Safety: compliant with LVD,EN60950-1 / EN62368-1 Compliant with EN50155/EN50121/E-mark
OS	
OS Support	Windows® 10 64-bit, Linux (support by request)

Ordering Information

Model Number	PCIe Slot	Thermal	AC Adaptor
MX1-10FEP-D-C246-FL	X16 + X1	Fanless	None
MX1-10FEP-D-C246-FL-AC300	X16 + X1	Fanless	300W AC to DC Adaptor
MX1-10FEP-D-C246-IF-AC300	X16 + X1	2 x Internal System Fan for PCIe slots	300W AC to DC Adaptor
MX1-10FEP-D-C246-IEF-AC300	X16 + X1	2 x Internal System Fan for PCIe slots 1 x External System Fan	300W AC to DC Adaptor

Packing List

Packing		
• 1 x MX1-10FEP-D	• 1 x 3-pin Terminal Block Connector	• 1 x 4-pin Terminal Block Connector
• 1 x CPU Cooler (passive)	• 1 x DVI to VGA converter	• 1 x Wall Mount Bracket
• 1 x Screw Pack (For HDD)	• 2 x 2-pin Terminal Block Connector	

Rugged

Fanless

Fanned

Rackmount